

■ Machine weight

Canopy Rubber	kg	980
Canopy Steel		—
Cabin Rubber		990
Cabin Steel		—

■ Standard bucket

Capacity	m ³	0.022
Width	mm	330

■ Engine

Model		KUBOTA Z602
Displacement	cc	599
Rated output/revolution	kW/min ⁻¹	7.8/2,400

■ Working range

Max. digging depth	mm	1,600	
Max. vertical digging depth	mm	1,395	
Max. digging height	mm	2,755	
Max. dumping height	mm	1,925	
Max. digging radius	mm	3,080	
Min. turning radius	front	mm	1,190
	swing	mm	960
Rear slew radius	mm	980	
Boom swing angle	deg.	L85° /R45°	

■ Dimensions

Overall length	mm	3,035
Overall width	mm	770(to)950
Overall height	mm	2,265
Dozer blade(width×height)	mm	750(or)950×185

■ Performance

Travel speed	km/h	1.8/3.5	
Slew speed	min ⁻¹	8.1	
Gradeability	deg.	30°	
Breakout force	Bucket	kN	8.3
	Arm	kN	5.8

■ Undercarriage

Ground pressure	Canopy Rubber	kPa	29.3
	Cabin Rubber	kPa	29.3
Shoe width×tumbler center	mm	180×970	
Type of travel motor		Piston	
Crawler tension system		Grease cylinder	

■ Hydraulic System

Type of hydraulic pump		Piston×2,Gear×1	
Main pump oil flow qty.	ℓ/min	10.8/10.8/7.2	
P.T.O. oil flow qty.	ℓ/min	21.6	
Main relief pressure	MPa	16.2/16.2/3.0	

■ Others

Hydraulic. oil	ℓ	10.5
Engine oil	ℓ	2.5
Fuel tank	ℓ	12.2
Cooling water	ℓ	5.0
Noise level Lwa/Lpa	dB	93/83